



Kyocera Technology

> PRINT > COPY > SCAN > FAX

CS 2552ci

COLOR MULTIFUNCTIONAL
SYSTEM

POWERFUL COLOR PERFORMANCE... CONNECTING PEOPLE AND INFORMATION.



Designed to impress, the Copystar CS 2552ci is the ultimate Color MFP for small business and distributed workgroups. As a flexible document processing hub, the Copystar CS 2552ci provides all the tools needed to easily and efficiently print, scan, copy and optionally fax. Indeed, document processing is a breeze with a large tablet-like color touch screen, and intuitive feature selections that speed job turnaround. Whether running routine copies or scanning to a network folder, the Copystar CS 2552ci is the ideal solution for your growing business.

- > Vivid Color and Black-and-White Imaging up to 25 Pages per Minute
- > Exceptional Print Quality at up to 1200 dpi
- > Scalable Paper Capacity for Longer Job Runs

- > Flexible Media Support and Paper Sizes up to 12" x 48"
- > Customizable 9" Color Touch Screen with Intuitive, Tablet-like Home Screen
- > Robust Portfolio of Business Applications that Can Optimize Your Document Workflow
- > Advanced Finishing Options for Professional Output, including a Space-Saving 500-Sheet Internal Finisher
- > Standard USB Host Interface for On-the-Go Printing and Scanning
- > Efficient Color Scanning up to 160 ipm
- > Convenient Wireless Printing and Scanning
- > Apple AirPrint®, Google Cloud Print™ and KYOCERA Mobile Print Compatible for a Mobile Printing Solution
- > KYOCERA Fleet Services, a secure cloud-based monitoring system, optimizes device uptime and reduces costs



Kyocera Technology

BASIC SPECIFICATIONS

Configuration: Color Multifunctional System – Print/Scan/Copy/Optional Fax
Pages Per Minute:
 Color and Black – Letter: 25 ppm, Legal: 15 ppm, Ledger: 12 ppm, 12" x 18": 12 ppm (print only)
Warm Up Time: 18 Seconds or Less (Power On)
First Page Out:
 Copy: 6.4 Seconds or Less Black, 8.5 Seconds or Less Color
 Print: 7.0 Seconds or Less Black, 9.2 Seconds or Less Color
Display: 9" Color Touch Screen Control Panel
Resolution: 600 x 600 dpi; 9600 dpi x 600 dpi; 1200 x 1200 dpi
Memory / Hard Disk Drive: 4 GB RAM / 8 GB SSD / 320 GB HDD Standard
Duplex: Standard Stackless Duplex Supports Statement to 12" x 18", 14 lb Bond – 166 lb Index (52 – 300gsm)
Standard Output Tray: Statement – 12" x 18" / 500 sheets; up to 12" x 48" Banner (Single Sheet)
Job Separator Output Tray: Statement – 12" x 18" / 100 sheets
Electrical Requirements: 120V, 60Hz, 12A; 220-240V, 50Hz, 7.2A
Typical Electricity Consumption (TEC): 120V: 1.1 kWh/week; 220V: 1.1 kWh/week
Dimensions: 23.70" W x 26.18" D x 31.10" H
Weight: 202.83 lbs
Maximum Monthly Duty Cycle: 100,000 Pages per Month

PAPER SUPPLY

Standard Paper Sources: Dual 500 Sheet Trays, 150 Sheet MPT, Auto Selection / Switching
Optional Paper Sources: Dual 500 Sheet Trays (PF-7100), Dual 1,500-sheet Trays (PF-7110); Side LCT; 3,000 Sheet Capacity Tray (PF-7120)
Paper Capacity: Standard: 1,150 Sheets; Maximum: 7,150 Sheets
Paper Size:
 Tray 1 – 5.5" x 8.5" – 8.5" x 14" (Statement to Legal); Tray 2 – 5.5" x 8.5" – 12" x 18", Custom Size; PF-7100: 5.5" x 8.5" – 12" x 18"; PF-7110, PF-7120: 8.5" x 11"; MPT: 5.5" x 8.5" – 12" x 18" (Multiple Sheets); Up to 12" x 48" Banner (Single Sheet)
Paper Weight: Trays / MPT: 14 lb Bond – 166 lb Index (52 – 300gsm)
Input Materials: Standard/Optional Drawer: Plain Paper, Bond Paper, Recycled Paper, Envelopes; MPT: Plain Paper, Bond Paper, Recycled Paper, Cardstock, Transparencies, Labels, Envelopes

SECURITY SPECIFICATIONS

Standard: Local Authentication, Network Authentication (IPsec, HTTPS, LDAP over SSL, SNMPv3); Secure Print (IPP over SSL); Scan to Email (POP3/SMTP over SSL); Scan to FTP (FTP over SSL); Scan to SMB/PC/USB; FTP over SSL
Optional: Data Security Kit (E): HDD Overwrite Mode, HDD Data Encryption

PRINT SPECIFICATIONS

Standard Controller: Freescale QorIQ T1024 (Dual Core) / 1.0GHz
PDLs / Emulations: PRESCRIBE, PCL6 (PCL-XL / PCL5c), KPDL3 (P53), XPS, OPEN XPS; Optional (UG-34): IBM ProPrinter, Line Printer, LQ-850
Print Resolution: Up to 1200 x 1200 dpi
Fonts: 136 KPDL3, 93 PCL6, 8 Windows Vista, 1 Bitmap
OS Compatibility: Windows: XP/Vista/7/8/8.1/10/Server 2003/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2; Novell NetWare 3.x/4.x/5.x/6.x; Mac OS 10.x; AirPrint Enabled; Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX (LPR)
Mobile Printing: Apple AirPrint®, Google Cloud Print™, KYOCERA Mobile Print

Interfaces: Standard: 10/100/1000BaseTX, Hi-Speed USB 2.0, 4 USB Host Interfaces, 2 Expansion Slots, Wireless LAN (communication distance 98.5 feet)
Optional: 10/100/1000BaseTX IB-50 for Dual NIC, IEEE 802.11b/g/n IB-51 for Wireless LAN Interface (communication distance 328.1 feet)
Network Print and Supported Protocols: TCP/IP, NetBEUI, IPv4, IPv6, IPsec, HTTP, LPD, FTP, IPP, RawPort, LLTD, SNTP, DHCP, SMTP, POP3, DNS, SNMPv1/v2, WSD Scan/Print
Drivers: KX Driver, PCL Mini Driver, KPDL Mini Driver, KX Driver for XPS, Network Fax Driver, TWAIN Driver, WIA Driver, PPD for MAC, PPD for Linux

SCAN SPECIFICATIONS

Scan Type: Color and Black & White Scanner
Scan Resolution: 600 dpi, 400 dpi, 300 dpi, 200 dpi, 200 x 100 dpi, 200 x 400 dpi
File Formats: TIFF (MMR compression), PDF (MMR compression), PDF (high compression), OpenXPS, XPS, JPEG
PDF Extension: Searchable PDF (OCR) Option
Scan Speeds (mono/color, @300 dpi):
 DP-7120: Simplex: 48 ipm B&W / 48 ipm Color; Duplex: 15 ipm B&W / 15 ipm Color
 DP-7100: Simplex: 80 ipm B&W / 80 ipm Color; Duplex: 48 ipm B&W / 48 ipm Color
 DP-7110: Simplex: 80 ipm BW / 80 ipm Color; Duplex: 160 ipm B&W / 160 ipm Color
Connectivity / Supported Protocols: 10/100/1000BaseTX, TCP/IP, Hi-Speed USB 2.0
Scanning Functions: Scan to Folder (SMB), Scan to Email, Scan to FTP, Scan to FTP over SSL, Scan to USB, WSD Scan, TWAIN Scan
Original Size: Through DP: Statement to Ledger (5.5" x 8.5" – 11" x 17"); Glass: Up to 11" x 17"
Drivers: TWAIN/WIA Driver

COPY SPECIFICATIONS

Copy Resolution: 600 x 600 dpi
Image Mode: Text, Photo, Text/Photo, Graphic/Map
Continuous Copy: 1 – 999 / Auto Reset to 1
Additional Features: Auto Magnification, Auto Paper Select, Auto Start, Auto Drawer Change, Interrupt Copy, Positive / Negative Reverse, Mirror Image, Rotate Copy, Border Erase, Split Copy, Electronic Sort, Margin Shift, Page Number, Form Overlay, XY Zoom, Prevent Bleed Through, Text Stamp, Bates Stamp, Blank Page Skip
Job Management: 1,000 Department Codes, Job Programs, Job Build, Shortcut Keys, Repeat Copy
Color Adjustment: One Touch, Hue, Auto Exposure, Sharpness
Magnification / Zoom: Full Size, 4 Reduction, 4 Enlargement Preset Ratios, 25 – 400% in 1% Increments
Document Box: Custom Box, Job Box, Removable Memory Box, Fax Box (with optional Fax System)

OPTIONAL DOCUMENT PROCESSORS*

Type / Capacity:
 DP-7120: Reversing Automatic Document Processor / 50 Sheets
 DP-7100: Reversing Automatic Document Processor / 140 Sheets
 DP-7110: Dual Scan Document Processor / 270 Sheets
Acceptable Originals: 5.5" x 8.5" – 11" x 17"
Acceptable Weights:
 DP-7120: Simplex: 14 lb Bond - 90 lb Index (45 – 160gsm); Duplex: 16 lb - 32 lb Bond (50 - 120gsm)
 DP-7100: Simplex: 13 lb Bond – 90 lb Index (35 – 160gsm); Duplex: 16 lb – 32 lb Bond (50 – 120gsm)
 DP-7110: Simplex: 13 lb Bond – 120 lb Index (35 – 220gsm); Duplex: 16 lb – 120 lb Index (50 – 220gsm)

OPTIONAL FAX SPECIFICATIONS

Fax Type: Fax System 12
Compatibility / Data Compression: G3 Fax / MMR, MR, MH, JBIG
Transmission Speed / Modem Speed: Less than 3 seconds / 33.6 Kbps
Fax Memory: Standard 170 MB
Driver: Network Fax Driver
Fax Functions: Network Fax, Duplex Transmission and Reception, Encrypted Transmission and Reception, Polling Transmission and Reception, Broadcast

OUTPUT & FINISHING OPTIONS

OPTIONAL 500 SHEET INTERNAL FINISHER DF-7100³
Stack / Staple Capacity: 500 Sheets / 50 Sheets (up to 24 lb Bond [90gsm])
Paper Size: 5.5" x 8.5" – 12" x 18"
Paper Weight: 14 lb Bond – 166 lb Index (52 – 300gsm)
Edge Staple Position: 3 Positions: Front 1 Staple, Edge 1 Staple, Face 2 Staples
Optional Punch: PH-7100 2 and 3 Hole Punch Unit, Supports 5.5" x 8.5" – 12" x 18"; 14 lb Bond – 166 lb Index (52 – 300gsm)
Dimensions: 19.60" W x 20.98" D x 6.73" H
OPTIONAL 1,000 SHEET FINISHER DF-7120^{3,4}
Stack / Staple Capacity: Main Tray: 1,000 Sheets / 50 Sheets (up to 24 lb Bond [90gsm])
Paper Size: 5.5" x 8.5" – 12" x 18"
Paper Weight: 14 lb Bond – 166 lb Index (52 – 300gsm)
Edge Staple Position: 3 Positions: Top Left, Bottom Left, Center Bind
Optional Punch: PH-7A 2 and 3 Hole Punch Unit, Supports 5.5" x 8.5" – 12" x 18"; 14 lb Bond – 166 lb Index (52 – 300gsm)
Dimensions: 21.57" W x 24.35" D x 41.34" H
OPTIONAL 4,000 SHEET FINISHER DF-7110^{3,4}
Stack / Staple Capacity: Main Tray (A): 4,000 Sheets; Sub Tray (B): 200 Sheets / 65 Sheets (up to 24 lb Bond [90gsm])
Paper Size: 5.5" x 8.5" – 12" x 18"
Paper Weight: 14 lb Bond – 166 lb Index (52 – 300gsm)
Edge Staple Position: 3 Positions: Top Left, Bottom Left, Center Bind
Optional Punch: PH-7A 2 and 3 Hole Punch Unit, Supports 5.5" x 8.5" – 12" x 18"; 14 lb Bond – 166 lb Index (52 – 300gsm)
Dimensions: 23.91" W x 26.32" D x 41.78" H
Optional Booklet Folder / Tri-fold Unit⁵: BF-730 Booklet Folder supports 8.5" x 11", 8.5" x 14", 11" x 17"; Fold booklet staple: 16 lb – 24 lb Bond (60 – 90gsm) 16 sheets; 25 lb – 28 lb Bond (91 – 105gsm) 13 sheets; Fold booklet no staple: 16 lb – 24 lb Bond (60 – 90gsm) 5 sheets; 25 lb Bond – 72 lb Index (91 – 120gsm) 3 sheets; 32 lb Bond – 110 lb Cover (121 – 256gsm) 1 sheet; Trifold supports 8.5" x 11" only: 16 lb – 24 lb Bond (60 – 90gsm) 5 sheets; 25 lb Bond – 72 lb Index (91 – 120gsm) 3 sheets; 16 lb – 28 lb Bond (60 – 105gsm) 1 sheet
Optional Multi-Bin Mailbox⁶: MT-730(B) includes 7 Trays; Supports 16 lb Bond – 90 lb Index (60 – 163gsm); Stack Capacity per bin: 100 Sheets: 5.5" x 8.5", 8.5" x 11"; 50 Sheets: 8.5" x 14", 11" x 17"

ADDITIONAL OPTIONS

Bridge Unit Attachment Kit (AK-7100), Banner Guide 10, Internet Fax Kit (A), Card Authentication Kit (B), Gigabit NIC (IB-50), Wireless LAN IEEE 802.11b/g/n (IB-51), ThinPrint (UG-33), Emulation (UG-34), Document Tray (DT-7100), Scan Extension Kit (A) for Searchable PDF/OCR, Keyboard Holder 10, Data Security Kit (E), Numeric Keypad (NK-7110)

¹ Requires PF-7100 or PF-7110
² Only 1 Document Processor can be installed
³ Only 1 Output Option can be installed
⁴ Requires Bridge Unit Attachment Kit (AK-7100)
⁵ Requires DF-7110

ONLY FROM KYOCERA

KYOCERA Document Solutions is a global leader in the digital imaging industry, with an award-winning line of document solutions that consistently set the standard for high performance, superior image quality, enhanced workflow applications, ease-of-use and durability.

Looking to streamline your document workflow? Kyocera offers a robust portfolio of business applications that seamlessly and securely integrate with our MFPs. To learn more about which business applications are right for your business, visit the Solutions section on our website.

Specifications and design are subject to change without notice. For the latest on connectivity, please visit www.copystar.com. MAC and AirPrint are trademarks of Apple, Inc. Google Cloud Print is a trademark of Google, Inc. PRESCRIBE, KX Driver, and Command Center RX are the trademarks of the Kyocera Companies. All other trademarks are the property of their respective owners.



KYOCERA Document Solutions America, Inc.
 Headquarters: 225 Sand Road, Fairfield, NJ 07004-0008, USA
 ©2016 KYOCERA Document Solutions America, Inc.
 IC# 855D400464

